

R507A

Version 2

Revision Date 10/01/2022

Print Date 01/09/2022

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : R507

Product Use Description : Refrigerant

Company : Beijing Starget Chemicals Co.,Ltd.
No.2 Jinzhan South Road,Chaoyang District,Beijing,China

For more information call : 0086-10-84340783
0086-10-84340782
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : **Medical: 0086-10-84340783 or 0086-10-84340782**
: **Transportation: 0086-10-84340783**
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : Liquefied gas

Color : Colorless

Odor : very faint sweet

Hazard Summary : Warning! Container under pressure. This product is not flammable at ambient temperatures and atmospheric pressure. Gas reduces oxygen available for breathing. Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating. Excessive exposure may cause central nervous system effects including drowsiness and dizziness. Excessive exposure may also cause cardiac arrhythmia. Rapid evaporation of the liquid may cause frostbite. Avoid contact with skin, eyes and clothing. At higher temperatures, (>250 C), decomposition products may include hydrofluoric acid (HF) and carbonyl halides. The ACGIH Threshold Limit Values (2007) for Hydrogen Fluoride are TLV-TWA 0.5 ppm and Ceiling Exposure Limit 2 ppm.

Potential Health Effects

Skin : Avoid skin contact with leaking liquid (danger of frostbite).
May cause frostbite.

R507A

Version 2

Revision Date 10/01/2022

Print Date 01/09/2022

- Irritating to skin.
- Eyes : Causes serious eye irritation.
May cause frostbite.
- Ingestion : Unlikely route of exposure.
Effects due to ingestion may include:
Gastrointestinal discomfort
- Inhalation : Gas reduces oxygen available for breathing.
Causes asphyxiation in high concentrations. The victim will
not realize that he/she is suffocating.
Excessive exposure may cause central nervous system
effects including drowsiness and dizziness. Excessive
exposure may also cause cardiac arrhythmia.
- Chronic Exposure : None known.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Chemical Name	CAS-No.	Concentration
Pentafluoroethane	354-33-6	50.00%
1,1,1-Trifluoroethane	420-46-2	50.00%

SECTION 4. FIRST AID MEASURES

- Inhalation : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.
- Skin contact : After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be

R507A

Version 2

Revision Date 10/01/2022

Print Date 01/09/2022

lukewarm, not hot. If symptoms persist, call a physician.

Ingestion : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

Notes to physician

Treatment : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-bitten areas as needed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : The product is not flammable.
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards during firefighting : Contents under pressure.
This product is not flammable at ambient temperatures and atmospheric pressure.
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.
Container may rupture on heating.
Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Rapid evaporation of the liquid may cause frostbite.
In case of fire hazardous decomposition products may be produced such as:
Hydrogen halides
Hydrogen fluoride
Carbon monoxide
Carbon dioxide (CO₂)
Carbonyl halides

Special protective equipment for firefighters : In the event of fire and/or explosion do not breathe fumes.
Wear self-contained breathing apparatus and protective suit.
No unprotected exposed skin areas.

R507A

Version 2

Revision Date 10/01/2022

Print Date 01/09/2022

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Wear personal protective equipment. Unprotected persons must be kept away.
Remove all sources of ignition.
Avoid skin contact with leaking liquid (danger of frostbite).
Ventilate the area.
After release, disperses into the air.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Avoid accumulation of vapours in low areas.
Unprotected personnel should not return until air has been tested and determined safe.
Ensure that the oxygen content is $\geq 19.5\%$.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
The product evaporates readily.
- Methods for cleaning up : Ventilate the area.

SECTION 7. HANDLING AND STORAGE**Handling**

- Handling : Handle with care.
Avoid inhalation of vapour or mist.
Do not get in eyes, on skin, or on clothing.
Wear personal protective equipment.
Use only in well-ventilated areas.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Follow all standard safety precautions for handling and use of compressed gas cylinders.
Use authorized cylinders only.
Protect cylinders from physical damage.
Do not puncture or drop cylinders, expose them to open flame or excessive heat.
Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
Do not remove screw cap until immediately ready for use.
Always replace cap after use.
- Advice on protection against fire and explosion : The product is not flammable.
Can form a combustible mixture with air at pressures above atmospheric pressure.

R507A

Version 2

Revision Date 10/01/2022

Print Date 01/09/2022

Storage

Requirements for storage areas and containers : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
 Keep containers tightly closed in a dry, cool and well-ventilated place.
 Storage rooms must be properly ventilated.
 Ensure adequate ventilation, especially in confined areas.
 Protect cylinders from physical damage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Do not breathe vapour.
 Avoid contact with skin, eyes and clothing.
 Ensure that eyewash stations and safety showers are close to the workstation location.

Engineering measures : General room ventilation is adequate for storage and handling.
 Perform filling operations only at stations with exhaust ventilation facilities.

Eye protection : Wear as appropriate:
 Safety glasses with side-shields
 If splashes are likely to occur, wear:
 Goggles or face shield, giving complete protection to eyes

Hand protection : Leather gloves
 In case of contact through splashing:
 Protective gloves
 Neoprene gloves
 Polyvinyl alcohol or nitrile- butyl-rubber gloves

Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).
 Wear cold insulating gloves/ face shield/ eye protection.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
 Wear a positive-pressure supplied-air respirator.
 Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
 For rescue and maintenance work in storage tanks use self-contained breathing apparatus.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
 Ensure adequate ventilation, especially in confined areas.
 Avoid contact with skin, eyes and clothing.

R507A

Version 2

Revision Date 10/01/2022

Print Date 01/09/2022

Remove and wash contaminated clothing before re-use.
Keep working clothes separately.

Exposure Guidelines—

Components	CAS-No.	Value	Control parameters	Update
Pentafluoroethane	354-33-6	TWA : time weighted average	4,900 mg/m3 (1,000 ppm)	2007

		TWA : time weighted average	(1,000 ppm)	
--	--	-----------------------------	-------------	--

1,1,1-Trifluoroethane	420-46-2	TWA : time weighted average	(1,000 ppm)	
-----------------------	----------	-----------------------------	-------------	--

		TWA : time weighted average	3,400 mg/m3 (1,000 ppm)	2007
--	--	-----------------------------	-------------------------	------

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquefied gas
 Color : Colorless
 Odour : very faint sweet

R507A

Version 2

Revision Date 10/01/2022

Print Date 01/09/2022

pH	:	neutral
Melting point/freezing point	:	not determined
Boiling point/boiling range	:	-46.7 °C
Flash point	:	not applicable
Evaporation rate	:	> 1 Method: Compared to CCl ₄ .
Lower explosion limit	:	Method: ASTM E-681 None
Upper explosion limit	:	Method: ASTM E-681 None
Vapour pressure	:	10,611 hPa at 21.1 °C(70.0 °F) 25,289 hPa at 54.4 °C(129.9 °F)
Vapour density	:	3.43 (Air = 1.0)
Density	:	1.07 g/cm ³ at 21.1 °C
Water solubility	:	1.5 g/l
Partition coefficient: n-octanol/water	:	log Pow: 1.48 Test substance: Ethane, pentafluoro- (HFC-125)
Ignition temperature	:	> 750 °C

R507A

Version 2

Revision Date 10/01/2022

Print Date 01/09/2022

Decomposition temperature : > 250 °C
Note: To avoid thermal decomposition, do not overheat.

Global warming potential : 3,850
(GWP)

Ozone depletion potential : 0
(ODP)

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Decomposes under high temperature.
Some risk may be expected of corrosive and toxic decomposition products.
Can form a combustible mixture with air at pressures above atmospheric pressure.
Do not mix with oxygen or air above atmospheric pressure.

Materials to avoid : Finely divided aluminium
Potassium
Calcium
Powdered metals
Aluminium
Magnesium
Zinc

Hazardous decomposition products : Halogenated compounds
Hydrogen fluoride
Carbonyl halides
Carbon oxides

Thermal decomposition : >250 °C
To avoid thermal decomposition, do not overheat.

Hazardous reactions : Hazardous polymerisation does not occur.
Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity
Pentafluoroethane : > 769000 ppm
Exposure time: 4 h
Species: rat

R507A

Version 2

Revision Date 10/01/2022

Print Date 01/09/2022

1,1,1-Trifluoroethane	:	LC50: > 540000 ppm Exposure time: 4 h Species: rat
		LC50: > 106 mg/l Exposure time: 4 h Species: rat
Sensitisation Pentafluoroethane	:	Cardiac sensitization Species: dogs Note: No-observed-effect level 75 000 ppm Lowest observable effect level 100 000 ppm
1,1,1-Trifluoroethane	:	Cardiac sensitization Species: dogs Note: 1,1,1,2-tetrafluoroethane (HFC-134a): Cardiac sensitisation threshold (dog): 80000 ppm.
Repeated dose toxicity Pentafluoroethane	:	Species: rat Application Route: Inhalation Exposure time: (4 Weeks) NOEL: 50000 ppm Subchronic toxicity
1,1,1-Trifluoroethane	:	Species: rat Application Route: Inhalation Exposure time: (90 d) NOEL: 40000 ppm Subchronic toxicity
Genotoxicity in vitro Pentafluoroethane	:	Test Method: Ames test Result: negative
1,1,1-Trifluoroethane	:	Test Method: Ames test Result: negative
	:	Cell type: Human lymphocytes Result: negative
	:	Cell type: Chinese Hamster Ovary Cells Result: negative
	:	Cell type: Human lymphocytes

R507A

Version 2

Revision Date 10/01/2022

Print Date 01/09/2022

Result: negative

Genotoxicity in vivo
1,1,1-Trifluoroethane

: Species: mouse
Cell type: Bone marrow
Application Route: Inhalation
Result: negative

Teratogenicity
Pentafluoroethane

: Species: rabbit
Application Route: Inhalation exposure
NOAEL, Teratog: 50,000 ppm
NOAEL, Maternal: 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.

Species: rat
Application Route: Inhalation exposure
NOAEL, Teratogens: 50,000 ppm
NOAEL, Maternal: 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.

1,1,1-Trifluoroethane

: Species: rat
Application Route: Inhalation exposure
NOAEL, Teratogens: 40,000 ppm
NOAEL, Maternal: 40,000 ppm
Note: Did not show teratogenic effects in animal experiments.

Species: rabbit
Application Route: Inhalation exposure
NOAEL, Teratogens: 40,000 ppm
NOAEL, Maternal: 40,000 ppm
Note: Did not show teratogenic effects in animal experiments.

Further information

: Acute toxicity Ethane, pentafluoro- (HFC-125): Cardiac sensitisation threshold (dog): 75000 ppm. 1,1,1-trifluoroethane (HFC-143a): Cardiac sensitisation threshold (dog): >250000 ppm. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Rapid evaporation of the liquid may cause frostbite. Irritating to eyes and skin. Avoid skin contact with leaking liquid (danger of frostbite). May cause cardiac arrhythmia.

SECTION 12. ECOLOGICAL INFORMATION

R507A

Version 2

Revision Date 10/01/2022

Print Date 01/09/2022

Biodegradability
Pentafluoroethane : Result: Not readily biodegradable.
Value: 5 %
Method: OECD 301 D

Further information on ecology

Additional ecological information : Accumulation in aquatic organisms is unlikely.
This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 3163
Proper shipping name : LIQUEFIED GAS, N.O.S.
(Pentafluoroethane, 1,1,1-Trifluoroethane)
Class : 2.2
Packing group
Hazard Labels : 2.2

IATA UN/ID No. : UN 3163
Description of the goods : LIQUEFIED GAS, N.O.S.
(Pentafluoroethane, 1,1,1-Trifluoroethane)
Class : 2.2
Hazard Labels : 2.2
Packing instruction (cargo aircraft) : 200
Packing instruction (passenger aircraft) : 200

IMDG UN/ID No. : UN 3163
Description of the goods : LIQUEFIED GAS, N.O.S.
(PENTAFLUOROETHANE, 1,1,1-TRIFLUOROETHANE)
Class : 2.2

R507A

Version 2

Revision Date 10/01/2022

Print Date 01/09/2022

Title III, Section 313.

Hazards : Acute Health Hazard
Sudden Release of Pressure Hazard

Spill or releases resulting in the loss of any ingredient at or about its RQ require immediate notification to the National Response Center and your local Emergency Planning Committee

WHMIS Classification : A: Compressed Gas
This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

Global warming potential : 3,850

Ozone depletion potential (ODP) : 0

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

R507A

Version 2

Revision Date 10/01/2022

Print Date 01/09/2022

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Starget Believes that the information and recommendations contained herein including data and statements are accurate as of the data hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other methods of use of the product and of the information referred to herein are beyond the control of STARGE Refrigerants. STARGET Refrigerants expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

Prepared by: Beijing Starget Chemical Co., Ltd.